Parker Pneumatic

Vane actuators provide the maximum amount of output torque from the smallest possible envelope size. They convert pneumatic pressure into rotary motion for a wide variety of industrial applications.

Two basic styles are available. Single vane models with a maximum rotation of 280°, while the double vane units produce twice the torque output from identical envelope dimensions and have a maximum rotation of 100°.

- Double acting actuators
- Single or double vane
- Compact smooth design
- Uniform torque in both directions
- Angle adjustment and sensors available.

Operating information

Туре		Double acting actuation
Standard rotation	Single vane	0 to 275°, size 10 to 11 0 to 280°, size 22 to 23
(tolerance ±1°)	Double vane	0 to 95°, size 10 to 11 0 to 100°, size 22 to 23
Temperature		-10°C to +80°C

Air supply Lubricated or non-lubricated

Pressure range 2 to 10 bar max

Basic Unit

Size	Max.rotation	Type	Shaft	Order code.
10	275°	Single		6V5100010F-275
	95°	Double	Not through	6V5100010F-095
11	275°	Single	rod	6V5200010F-275
	95°	Double	_	6V5200010F-095
22	280°	Single		6V1300030F-280
	100°	Double Throu	Through	6V1300030F-100
33	280°	Single	rod	6V2400030F-280
	100°	Double	_	6V2400030F-100

Angle adjustment and sensor kits

Size	Options	Order code.	
22	Angle adjustment	6V03570	
	kit Angle editetment		
	Angle adjustment	6V03575	
	kit with sensors PNP		
	Angle adjustment	6V03576	
	kit with sensors NPN		
33	Angle adjustment	6V04570	
	Kit	0004570	
	Angle adjustment	_ 6V04575	
	kit with sensors PNP	004575	
	Angle adjustment	6 V 04576	
	kit with sensors NPN		

Complete with angle adjustment and sensors

Size	Max.rotation	Type	Shaft	Order code.
22	220°	Single	Angle adjustment	6V1357630F-220
	100°	Double	kit	6V1357730F-100
	220°	Single	As above + PNP	6V1357635F-220
	100°	Double	Sensors + plug	6V1357735F-100
	220°	Single	As above + NPN	6V1357636F-220
	100°	Double	Sensors + plug	6V1357736F-100
33	220°	Single	Angle adjustment	6V2457630F-220
	100°	Double	kit	6V2457730F-100
	220°	Single	As above + PNP	6V2457635F-220
	100°	Double	Sensors + plug	6V2457735F-100
	220°	Single	As above + NPN	6V2457636F-220
	100°	Double	Sensors + plug	6V2457736F-100



